



CT341 系列产品采用 PVC 绝缘带缠绕绝缘，工艺简单，成本低。

产品经过全新的设计，采用优秀的结构，外形美观大方。并根据需要可以配备一次性安装使用的端子盖板，对端子的接线安全持续提供可靠标识。

全系列产品均采用高导磁硅钢材料、优质漆包圆铜线生产，准确级优，准确限值系数高，且结构紧凑，安装方便，广泛的用在配电系统中。

产品采用端子输出，可以采用并联端子输出结构，S1 和 S2 端均有两个并联的输出端子，方便接线。也可以根据需要，进行多变比设计，以适应更多的安装环境。

型号	等级				10P5						10P10					10P15			
	RATIO	ID	OD	VA	5	7.5	10	15	20	30	5	7.5	10	15	20	5	7.5	10	15
341003	100/5	30	95	厚度mm	50	60	75	100	130	-	85	100	-	-	-	-	-	-	-
	120/5	30	95		50	60	70	95	120	-	80	105	-	-	-	-	-	-	-
	150/5	30	95		40	50	60	80	110	-	65	90	110	-	-	-	-	-	-
	200/5	28	95		40	40	40	55	65	-	60	60	70	-	-	-	-	-	-
341103	150/5	40	100	厚度mm	50	55	65	85	100	-	75	100	110	120	-	-	-	-	-
	200/5	40	100		40	40	50	60	70	-	55	70	85	110	-	-	-	-	-
	250/5	40	95		40	40	50	60	70	-	50	70	85	110	-	75	95	-	-
	300/5	40	95		35	40	40	60	65	85	50	60	70	95	-	70	85	105	-
341203	200/5	45	95	厚度mm	40	50	60	80	100	115	75	95	110	-	-	-	-	-	-
	250/5	45	95		40	50	60	70	85	110	60	75	90	115	-	85	110	-	-
	300/5	45	95		35	40	40	60	70	95	50	65	80	100	-	70	90	-	-
	400/5	45	95		35	40	40	60	60	85	50	55	65	85	-	65	80	95	-
341303	400/5	58	100	厚度mm	35	40	40	60	70	90	60	65	80	100	-	75	95	110	-
	500/5	58	100		35	40	40	60	60	80	50	60	70	85	110	70	80	95	-
	600/5	57	100		35	35	40	50	50	70	50	50	60	80	90	60	75	85	110
	800/5	55	104		35	35	35	40	50	60	40	50	50	60	80	55	65	75	90
341403	600/5	70	114	厚度mm	35	35	40	50	50	70	50	50	60	80	95	70	80	90	110
	800/5	70	114		35	35	35	40	40	55	40	40	50	60	70	50	60	70	85
	1000/5	68	116		35	35	35	35	40	50	35	40	50	55	65	50	55	65	80
	1200/5	67	117		35	35	35	35	35	40	35	40	40	50	60	40	50	55	65
341503	800/5	85	125	厚度mm	35	35	35	40	50	60	40	50	55	65	80	60	65	75	95
	1000/5	83	127		35	35	40	40	40	60	40	40	50	60	75	50	60	70	80
	1200/5	83	128		35	35	35	35	40	40	35	35	40	45	60	40	50	60	65
	1600/5	82	130		35	35	35	35	35	40	35	35	35	40	50	40	50	50	65
341603	1200/5	110	152	厚度mm	35	35	35	35	40	50	40	40	50	45	65	50	60	65	80
	1600/5	110	155		35	35	35	35	35	40	35	35	35	40	50	35	50	50	60
	2000/5	108	158		30	30	30	30	30	30	35	35	35	40	40	35	40	50	50
	2500/5	106	162		30	30	30	30	30	30	35	35	35	35	40	35	35	40	50
341703	1600/5	120	165	厚度mm	30	30	30	35	35	40	35	40	40	45	60	50	50	55	65
	2000/5	120	165		30	30	30	35	35	40	35	35	40	40	50	40	40	50	50
	2500/5	118	168		30	30	30	35	35	35	35	35	35	40	40	35	40	40	50
	3000/5	116	170		30	30	30	35	35	35	35	35	35	40	40	35	40	40	50
341803	2000/5	130	175	厚度mm	30	30	30	35	35	40	35	35	40	40	50	40	50	50	60
	2500/5	130	175		30	30	30	35	35	40	35	35	35	40	40	35	40	40	50
	3000/5	128	178		30	30	30	35	35	35	35	35	35	40	40	35	40	40	50
	3500/5	126	180		30	30	30	35	35	35	35	35	35	40	40	35	35	40	40
341903	2500/5	140	185	厚度mm	35	35	35	35	40	40	35	35	40	40	50	35	40	50	60
	3000/5	140	185		35	35	35	35	35	40	35	35	35	40	40	35	40	40	50
	3500/5	138	188		35	35	35	35	35	35	35	35	35	40	40	35	35	40	40
	4000/5	136	190		35	35	35	35	35	35	35	35	35	40	40	35	35	40	40